




---

 PRODUCT-DETAILS

# OT1250E04CP

## OT1250E04CP CHANGE-OVER SWITCH




---

**General Information**

Extended Product Type	OT1250E04CP
Product ID	1SCA022872R1250
EAN	6417019338941
Catalog Description	OT1250E04CP CHANGE-OVER SWITCH
Long Description	1250A, 4 pole manual change-over switch including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and II- positions and when padlocked.

---

**Circular Value**

Environmental Information	1SCC303050D0201
---------------------------	-----------------

---

**Material Compliance**

Conflict Minerals Reporting Template	9AKK108467A5658
--------------------------------------	-----------------

(CMRT)

REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

## Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0208

## Dimensions

Product Net Width	480 mm 18.9 in
Product Net Height	306 mm 12.05 in
Product Net Depth / Length	309 mm 12.17 in
Product Net Weight	42.52 kg 93.74 lb

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 1250 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 1250 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 710 kW (500 V) 900 kW (690 V) 1200 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 1250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time	for 1 s 50 kiloampere rms

Withstand Current Low Voltage (I <sub>cw</sub> )	
Power Loss	29 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Terminal Width	50 mm
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Transition Type	Open

**Technical UL/CSA**

Ampere Rating	1250 A
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m

**Environmental**

Environmental Information	1SCC303050D0201
---------------------------	-----------------

**Certificates and Declarations**

Declaration of Conformity - CE	1SCC303015D2702
DNV Certificate	1SCC303138D0201

**Container Information**

Package Level 1 Units	1 piece
Package Level 1 Width	339 mm 13.35 in
Package Level 1 Depth / Length	534 mm 21.02 in
Package Level 1 Height	338 mm 13.31 in
Package Level 1 Gross Weight	44.52 kg 98.15 lb
Package Level 1 EAN	6417019338941

**Classifications**

Object Classification	Q
-----------------------	---

Code	
ETIM 8	EC000216 - Switch disconnect
ETIM 9	EC000216 - Switch disconnect (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3600148

---

## Categories

---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

