



PRODUCT-DETAILS

# OVR T2 1N 40-275 P QS

## OVR T2 1N 40-275 P QS Surge Protective Device



General Information	
Extended Product Type	OVR T2 1N 40-275 P QS
Product ID	2CTB803972R1100
EAN	3660308519696
Catalog Description	OVR T2 1N 40-275 P QS Surge Protective Device
Long Description	Surge protective devices SPD type 2 protect low-voltage consumer systems against surge voltages as they are tested as SPD type 2 according to IEC 61643-11. The devices are compatible with the System pro M compact series. The SPD with "TS" are optionally equipped with a auxiliary contact.

Technical	
Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TT TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U <sub>r</sub> )	230 V AC
Nominal AC Voltage of the System (U <sub>o</sub> )	230 / 400 V
Voltage Rating DC	350 V
Voltage Protection Level (U <sub>p</sub> )	1.5 kV (L-N) 1.25 kV

Maximum Continuous Operating Voltage ( $U_c$ )	(N-PE) 1.4 kV (L-PE) 275 V
Temporary Overvoltage Test Value ( $U_T$ )	(L-N) 337 V (N-PE) 1200 V
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	100 kA
Discharge Current	Nominal (8 / 20 $\mu$ s) 20 kA I (max, 8 / 20 $\mu$ s) 40 kA
Impulse Current	I (imp, 10 / 350 $\mu$ s) 2 kA
Short Circuit Withstand Icc	100 kA
Power Loss	17 mW
Arrester Class	II
Number of Protected Poles	2
Number of Poles	2
Number of Conductors	2
Position of Neutral Terminals	Right
Transmission Standard Version	Optic Plug-in
Mounting Type	DIN-Rail
Product Type	QS
Options Provided	Residential, commercial building.
Auxiliary Circuit Load	Minimum - Maximum -
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	2 modular spacing

## Material Compliance

RoHS Information	9AKK108466A4410
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20220317
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20231212
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

## Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35.6 mm
Product Net Height	88 mm
Product Net Depth / Length	58 mm
Product Net Weight	0.24 kg

---

## Ordering

---

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	250 g

---



---

## Certificates and Declarations

---

CB Certificate	2CTC432024G1701
CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4410

---



---

## Installation

---

Instructions and Manuals	2CTC432096M1701
--------------------------	-----------------

---



---

## Popular Downloads

---

Data Sheet, Technical Information	2CTC432219D0201
Mechanical Drawings	2CTC800021F1100.pdf 2CTC800021F1101.dxf 2CTC800021F1102.stp 2CTC800021F1103.igs

---



---

## Classifications

---

ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141DCC

---



---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II



360°