









Control stations - Harmony XAL


Unit price (incl.VAT) in VND

Complete stations with 1 pushbutton, selector switch or key switch



		1 Start or Stop function					
		1 Flush green p/b		1 Flush red p/b			
Contact	Marking	Reference	Unit Price	Reference	Unit Price		
		N/O	I	XALD102	638.000	-	
		N/C	O			XALD112	638.000
		1 Start-Stop function					
		Black handle		Key n° 455 (key withdrawal LH pos.)			
Contact	Marking	Reference	Unit Price	Reference	Unit Price		
		N/O	O-I	XALD134	808.500	XALD144	1.138.500
		Emergency stop (2) (light grey RAL 7035 base with yellow RAL 1012 lid)					
Contact		Reference	Unit Price	Reference	Unit Price		
		N/C + N/C		XALK178F	786.500	XALK188F	973.500
		N/C + N/O		XALK178E	761.200	XALK188E	917.400
		N/C +N/C + N/O		XALK178G	891.000	XALK188G	1.061.500
		Start-Stop functions					
		1 Flush green p/b		1 Flush red p/b			
Contact	Marking	Reference	Unit Price	Reference	Unit Price		
		N/O + N/C	O-I	XALD213	1.303.500	XALD363M 230Vac	2.150.500
		Start - stop		XALD215	1.303.500		

Empty control stations

For XB7 range

	Number of holes	Reference	Unit Price
	1	XALE1	297.000
	2	XALE2	308.000
XALE02	3	XALE3	319.000

For XB4/ XB5 range

		Light grey RAL 7035 based Dark grey RAL 7016 lid		Light grey RAL 7035based Yellow RAL 1021 lid	
		Reference	Unit Price	Reference	Unit Price
					
	1	XALD01	242.000	XALK01	253.000
	2	XALD02	352.000	XALK02	374.000
	3	XALD03	429.000	XALK03	462.000
XALK01	4	XALD04	588.500	XALK04	594.000
XALD02	5	XALD05	841.500	XALK05	671.000

Unit price (incl.VAT) in VND

For control of hoist motors

Single-speed hoist motors



Number of operators	Type of operators	Per direction	E.stop	Reference	Unit Price
2 mechanically interlocked	Standard	1N/O	-	XACA201	2.288.000
		1N/C + 1N/O	-	XACA205	2.508.000
	Booted	1N/O	-	XACA211	2.700.500
		1N/C + 1N/O	-	XACA215	2.926.000
2 mechanically latching Ø 30 mm E Stop	Standard	1N/O	N/C	XACA2014	3.399.000
		1N/C + 1N/O	N/C	XACA2154	3.883.000

Two-speed hoist motors



Number of operators	Type of operators	Per direction	E.stop	Reference	Unit Price
2 mechanically interlocked	Standard	2 steps,	-	XACA207	2.904.000
	Booted	1N/O + 1N/O	-	XACA217	2.992.000
+ 1 trigger action	Standard	staggered	N/C	XACA2074	4.081.000

For control of motors

Single-speed motors




Number of Operators	Per direction	E.stop	Reference	Unit Price
2 mechanically interlocked	N/O	-	XACA271	1.732.500
	N/C+N/O	-	XACA281	1.980.000
+ 1 trigger action	N/O	N/C	XACA2714	3.344.000
latching Ø 30 mm E-Stop	N/C+N/O	N/C	XACA2814	3.421.000
4 mechanically interlocked	N/O	3 N/C	XACA27141	4.356.000
+ † trigger action	N/C+N/O	3N/C	XACA28141	4.702.500

Two-speed motors




Number of Operators	Per direction	E.stop	Reference	Unit Price
4 mechanically interlocked	N/O	-	XACA491	3.888.500
+ 1 trigger action	N/C+N/O	N/C	XACA4914	4.906.000
	N/O	3 N/C	XACA49141	5.505.500

Joystick controller (with 54 mm long operating shaft) - complete products



One contact per 1 direction - 1 speed

Operation	Sprint return to zero position	Contact per direction	Reference	Unit Price
2-dreicfn	Without	1NO	XD5PA12	1.716.000
2-dreicfn	With	1 NO	XD5PA22	1.826.000
4-dreicfn	Without	1NO	XD5PA14	3.311.000
4-dreicfn	With	1NO	XD5PA24	3.547.500



Two contact per 1 direction - 2 speed

Number of operators	Sprint return to zero position	Contact per direction	Reference	Unit Price
2-dreicfn	Without	2NO	XD2GA8241	5.115.000
2-dreicfn	With	2NO	XD2GA8251	4.983.000
4-dreicfn	Without	2NO	XD2GA8441	7.496.500
4-dreicfn	With	2NO	XD2GA8451	10.444.500

LED Indicator bank Ø 60mm

With 2, 3 or 4 illuminated signalling units,
coloured LEDs and clear lenses

Voltage: 24Vac/dc

Multi mounting, specially of foldable bracket

Đèn tầng cảnh báo Ø 60mm

Đèn 2,3,4 tầng, LED màu và ống nhựa bọc bên ngoài trong suốt

Điện áp: 24Vac/dc

Đế đèn đa dạng, đặc biệt có dạng để gấp lại được

Unit price (incl.VAT) in VND

Compact tower light XVG Ø 60 mm, 24VACJDC



With base mounting

Degree of protection	Buzzer	Signalling colors	Reference	Unit Price
IP53	No	Red, Green	XVGB2W	2.068.000
IP53	No	Red, Amber, Green	XVGB3W	2.326.500
IP53	No	Red, Amber, Green, Blue	XVGB4W	3.030.500
IP42	Yes	Red, Green	XVGB2SW	2.480.500
P42	Yes	Red, Amber, Green	XVGB3SW	2.860.000
IP42	Yes	Red, Amber, Green, Blue	XVGB4SW	3.399.000

With direct aluminium tube mounting

Degree of protection	Buzzer	Signalling colors	Reference	Unit Price
IP23	No	Red, Green	XVGB2T	1.870.000
IP23	No	Red, Amber, Green	XVGB3T	2.403.500
P23	Yes	Red, Green	XVGB2ST	2.673.000
IP23	Yes	Red, Amber, Green	XVGB3ST	2.909.500
IP23	Yes	Red, Amber, Green, Blue	XVGB4ST	3.674.000

With aluminium tube mounting and L-bracket

Degree of protection	Buzzer	Signalling colors	Reference	Unit Price
IP23	No	Red, Green	XVGB2	2.200.000
IP23	No	Red, Amber, Green	XVGB3	2.480.500
IP23	No	Red, Amber, Green, Blue	XVGB4	2.723.600
IP23	Yes	Red, Green	XVGB2S	2.640.000
IP23	Yes	Red, Amber, Green	XVGB3S	2.992.000
IP23	Yes	Red, Amber, Green, Blue	XVGB4S	3.300.000

With aluminium tube mounting and fixing plate

Degree of protection	Buzzer	Signalling colors	Reference	Unit Price
IP53	No	Red, Green	XVGB2H	2.200.000
IP53	No	Red, Amber, Green	XVGB3H	2.480.500
IP53	No	Red, Amber, Green, Blue	XVGB4H	2.981.000
IP42	Yes	Red, Green	XVGB2SH	2.640.000
IP42	Yes	Red, Amber, Green	XVGB3SH	2.992.000
IP42	Yes	Red, Amber, Green, Blue	XVGB4SH	3.580.500

With aluminium tube mounting and foldable bracket

Degree of protection	Buzzer	Signalling colors	Reference	Unit Price
IP40	No	Red, Green	XVGB2M	2.420.000
IP40	No	Red, Amber, Green	XVGB3M	2.728.000
IP40	No	Red, Amber, Green, Blue	XVGB4M	3.415.500
IP40	Yes	Red, Green	XVGB2SM	2.904.000
IP40	Yes	Red, Amber, Green	XVGB3SM	3.283.500
IP40	Yes	Red, Amber, Green, Blue	XVGB4SM	3.599.200

Compact tower light XVG Ø 60 mm with USB port - multi color

Degree of protection	Buzzer	Signalling colors	Reference	Unit Price
With base mounting				
IP42	Yes	Multi-color Setting by Software	XVGU3SWV	4.136.000
With aluminium tube mounting and fixing plate				
IP42	Yes	Multi-color Setting by Software	XVGU3SHAV	4.675.000

Indicator bank Ø 45mm optimum
 Electric shock protection conforming to
 IEC 61140, IEC 60947-1 and IEC 60947-5-1
 Voltage consumption 24Vac/dc, 120Vac, 230Vac
 2-4 illuminated units & multi-choice flashing units

Đèn hiệu cảnh báo nhiều tầng Ø 45mm
 Bảo vệ chống giật theo tiêu chuẩn quốc tế:
 IEC 61140, IEC 60947-1 và IEC 80947-5-1
 Điện áp tiêu thụ: 24Vac/dc, 120Vac, 230Vac
 Từ 2-4 phần tử, có chỉ định phần tử cảnh báo.

Unit price (incl.VAT) in VND

Complete, pre-wired tower light XVM Ø 45 mm / IP42



Light source (included) - Incandescent BA 15d bulb, 5 W max. with Buzzer

Type of Contacts	2 signalling units + integral buzzer Steady light		3 signalling units + integral buzzer Steady light		3 signalling units + integral buzzer Steady light + "Flash"	
	Reference	Unit Price	Reference	Unit Price	Reference	Unit Price
24 V AC/DC	XVMB2RGSSB	3.300.000	XVMB2RAGSSB	4.400.000	XVMB2R6AGSSB	5.500.000
120 V AGDC (bulb) - 120 V AC (LED)	XVMG2RGSSB	-	XVMG2RAGSSB	3.844.500	-	-
230 V ACIDC (bulb) -230 V AC (LED)	XVMM2RGSSB	3.520.000	XVMM2RAGSSB	4.180.000	XVMM2R6AGSSB	-

Breakdown of the reference for a pre-assembled indicator bank (1)



Voltage	XVM	4 units			
		1 units	2 units	3 units	4 units
24 V	B				
120V	G				
230 V	M				
Light source	Incandescent bulb	1			
	LED	2			
Illuminated unit	Red	R	R	R	R
	Orange	A	A	A	A
	Colour	Green	G	G	G
	Blue	B	B	B	B
	Clear	C	C	C	C
	Steady		(3)	(3)	(3)
Signalling	Flashing	5	5	5	5
	"Flash"	6	6	6	6
Buzzer	Without				(3)
	With				S

- (1) This table is purely for information and must not be used to create a product reference.
- (2) "Flash" discharge tube to be ordered separately,
- (3) Not indicated, default value.

Complete, pre-wired tower lights, Steady light, Ø 40 mm / Up to IP54



Light source (included) - LED - Without buzzer

Type of Contacts	Base mounting 24V AC/DC		Support tube mounting, 17 mm 24V ACIDC		Support tube mounting, 17 mm 100-240V AC	
	Reference	Unit Price	Reference	Unit Price	Reference	Unit Price
Red	XVC4B1K	3.910.500	XVC4B1	4.158.000	XVC4M1	8.255.500
Orange/Red	XVC4B2K	4.237.200	XVC4B2	5.318.500	XVC4M2	9.233.400
Green/Orange/Red	XVC4B3K	5.533.000	XVC4B3	5.681.500	XVC4M3	9.709.700
Blue/Green/Orange/Red	XVC4B4K	6.963.000	XVC4B4	6.226.000	XVC4M4	-
Clear/Blue/Green/Orange/Red	XVC4B5K	7.606.500	XVC4B5	8.151.000	XVC4M5	-

Complete, pre-wired tower lights, Steady light, Ø 60 mm / Up to IP54



Light source (included) - LED - Without buzzer

Type of Contacts	Base mounting 24V AC/DC		Support tube mounting, 22mm 24V AC/DC		Support tube mounting, 22 mm 100-240V AC	
	Reference	Unit Price	Reference	Unit Price	Reference	Unit Price
Red	XVC6B1K	4.195.400	XVC6B1	6.734.200	XVC6M1	9.411.600
Orange/Red	-	-	XVC6B2	7.221.500	XVC6M2	10.461.000
Green/Orange/Red	XVC6B3K	6.990.500	XVC6B3	8.173.000	XVC6M3	11.287.100
Blue/Green/Orange/Red	-	-	XVC6B4	8.827.500	XVC6M4	12.274.900
Clear/Blue/Green/Orange/Red	XVC6B5K	10.070.500	XVC6B5	11.555.500	XVC6M5	-