

# Product datasheet

Specifications



## Auxiliary contact, GoPact MCCB 125/200/250, 1 NO/NC contact type, circuit breaker status OF/SD

G12-25AUX240

### Main

Range of product	GoPact MCCB
product or component type	Auxiliary contact
Device short name	OF and SD
Device application	Breaker status monitoring
Range compatibility	GoPact MCCB 125 GoPact MCCB 200 GoPact MCCB 250
Signal contacts composition	1 NO/NC

### Complementary

Local signalling	ON/OFF indication for open/close Trip indicator for voltage release indication Trip indicator for electrical fault
mounting mode	By screws
[I <sub>th</sub> ] conventional free air thermal current	6 A
[U <sub>e</sub> ] rated operational voltage	240 V AC
[I <sub>e</sub> ] rated operational current	AC-12: 6 A at 12 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 240 V AC 50/60 Hz AC-14: 6 A at 12 V AC 50/60 Hz AC-14: 6 A at 24 V AC 50/60 Hz AC-14: 6 A at 48 V AC 50/60 Hz AC-14: 6 A at 110 V AC 50/60 Hz AC-14: 6 A at 240 V AC 50/60 Hz DC-12: 6 A at 12 V DC DC-12: 5 A at 24 V DC DC-12: 1 A at 48 V DC DC-12: 0.5 A at 110 V DC DC-12: 0.25 A at 220 V DC
Mechanical durability	10000 cycles
Auxiliary connection terminal	Pre-wired 0.5 mm <sup>2</sup>
Cable length	500 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.5 cm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Package 1 Length</b>	4.8 cm
<b>Package 1 Weight</b>	600 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	60
<b>Package 2 Height</b>	30 cm
<b>Package 2 Width</b>	30 cm
<b>Package 2 Length</b>	40 cm
<b>Package 2 Weight</b>	4.041 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	720
<b>Package 3 Height</b>	60 cm
<b>Package 3 Width</b>	60 cm
<b>Package 3 Length</b>	80 cm
<b>Package 3 Weight</b>	56.992 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

✓ Reach Free Of Svhc

---

✓ Mercury Free

---

✓ Rohs Exemption Information Yes

---

✓ Pvc Free

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant  
[EU RoHS Declaration](#)

---

**China Rohs Regulation** [China RoHS declaration](#)

---

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---