Product datasheet

Specifications





MX shunt trip, GoPact MCCB 200/250, 240VAC 50/60Hz

G20-25SHT240AC

Main

Range of product	GoPact MCCB
product or component type	Voitage release
Device short name	MX
Device application	Control
Range compatibility	GoPact MCCB 200 GoPact MCCB 250
Voltage release type	Shunt trip
[Uc] control circuit voltage	240 V AC 50/60 Hz

Complementary

Threshold tripping voltage	0.71.1 Un opening
Max supply pick-up power consumption	5 VA
Response time	25 ms

Packing Units

PCE
1
6.5 cm
8.5 cm
4.8 cm
100 g
S02
20
15 cm
30 cm
40 cm
2.315 kg
P06
320
60 cm
60 cm
80 cm

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Package 3 Weight

45.540 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information