# **Product datasheet**

Specifications





# Vivace telephone + cat 5e data outlet - 1 gang - with shutter

KB32TS\_RJ5E

#### Main

| Range                     | Vivace                |
|---------------------------|-----------------------|
| Device short name         | KB32                  |
| product or component type | Data/telephone socket |
| device presentation       | Complete mechanism    |
| Cover frame colour tint   | White                 |
| Colour tint               | White                 |
| Telephone socket type     | RJ11                  |

# Complementary

| Number of gangs   | 2 gangs   |
|-------------------|---|
| Tightening torque | 0.4 N.m   |
| Material          | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Polycarbonate: base |
| device mounting   | Flush   |
| mounting support  | Wall mounted  |
| Fixing mode       | By screw M3.5   |
| Fixing center     | 60.3 mm   |
| Width             | 86 mm   |
| Height            | 86 mm   |
| Projecting depth  | 8 mm  |
| Embedding depth   | 35 mm   |
| Main colour tint  | White   |

#### Environment

| Ambient air temperature for operation | -540 °C    |
|---------------------------------------|------------|
| Relative humidity                     | 095 %      |
| Environmental characteristic          | Indoor use |
| Standards                             | FCC        |

#### **Packing Units**

Unit Type of Package 1

Number of Units in Package 1

PCE

1

| Package 1 Height             | 8.6 cm   |
|------------------------------|----------|
| Package 1 Width              | 4 cm     |
| Package 1 Length             | 8.6 cm   |
| Package 1 Weight             | 170.5 g  |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 8        |
| Package 2 Height             | 15 cm    |
| Package 2 Width              | 19 cm    |
| Package 2 Length             | 8 cm     |
| Package 2 Weight             | 1.434 kg |
| Unit Type of Package 3       | CAR      |
| Number of Units in Package 3 | 80       |
| Package 3 Height             | 21 cm    |
| Package 3 Width              | 31.5 cm  |
| Package 3 Length             | 50 cm    |
| Package 3 Weight             | 13890 g  |

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance



Rohs Exemption Information

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |