


# Product datasheet

Specifications



## 16AX 250V 2GANG 1 WAY SWITCH

KB32\_1\_WE

! Discontinued

### Main

Range	Vivace
product or component type	Switch
Device short name	KB32
Device application	Control switch
Number of rocker	2
Additional switch application	On/off switching
Switch function	1-way
Colour tint	White

### Complementary

Technology type	Electromechanical
device presentation	Complete product
Actuator	Rocker
Number of gangs	2 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Surface finish	Glossy
Surface treatment	Untreated
[Ue] rated operational voltage	220...250 V
Type of packing	Plastic bag
Network type	AC
Quantity per set	1
Rated current	16 AX
Sale per indivisible quantity	1
Projecting depth	8 mm
device mounting	Flush
mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm

Connections - terminals	Screw terminal
Embedding depth	25 mm
Number of terminals	4
Rated current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent 16 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50/60 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	4 screw terminals
Terminal identifier	L1 COM L2
Tightening torque	0.4 N.m
Clamping connection capacity	<= 2.5 mm <sup>2</sup> for rigid or stranded cable(s)
Wire stripping length	12 mm
Width	86 mm
Height	86 mm
Depth	37 mm

## Environment

Standards	IEC 60669-1 MS IEC 60669-1 SS 227
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Operating altitude	0...2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	8.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	74 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	8 cm
Package 2 Weight	636 g
Unit Type of Package 3	CAR

<b>Number of Units in Package 3</b>	80
<b>Package 3 Height</b>	21 cm
<b>Package 3 Width</b>	31.5 cm
<b>Package 3 Length</b>	50 cm
<b>Package 3 Weight</b>	6908 g

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations