


Bảng thông số sản phẩm

Thông số kỹ thuật



Contactor, Easy TeSys Control, LC1E, 3P(3NO), AC-3, $\leq 440\text{V}$, 50A, 110V AC coil, 50Hz

LC1E50F5

Main

Range	Easy TeSys
Range of product	Easy TeSys Control
product or component type	Contactor
Device short name	LC1E
contactor application	Resistive load Motor control
Utilisation category	AC-3 AC-1
poles description	3P
[Ue] rated operational voltage	Power circuit: $\leq 690\text{ V AC } 50/60\text{ Hz}$
[Ie] rated operational current	50 A (at $\leq 55\text{ }^\circ\text{C}$) at $\leq 440\text{ V AC AC-3}$ for power circuit 70 A (at $\leq 55\text{ }^\circ\text{C}$) at $\leq 440\text{ V AC AC-1}$ for power circuit
[Uc] control circuit voltage	110 V AC 50 Hz

Complementary

Motor power kW	15 kW at 220...230 V AC 50/60 Hz 22 kW at 380...400 V 25 kW at 415 V 30 kW at 440 V 30 kW at 500 V 33 kW at 660...690 V
Pole contact composition	3 NO
[Ith] conventional free air thermal current	70 A (at $55\text{ }^\circ\text{C}$)
Irms rated making capacity	500 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	400 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	400 A $40\text{ }^\circ\text{C}$ - 10 s for power circuit 208 A $40\text{ }^\circ\text{C}$ - 60 s for power circuit 84 A $40\text{ }^\circ\text{C}$ - 600 s for power circuit
Associated fuse rating	10 A gG at $\leq 690\text{ V}$ coordination type 1 for control circuit conforming to IEC 60947-5-1 100 A gG at $\leq 690\text{ V}$ coordination type 1 for power circuit
Average impedance	1.5 mOhm - Ith 70 A 50 Hz for power circuit
Power dissipation per pole	3.8 W AC-3 7.4 W AC-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3

[Uimp] rated impulse withstand voltage	6 kV coil not connected to the power circuit conforming to IEC 60947
Mechanical durability	5000000 cycles
Electrical durability	350000 cycles AC-1 900000 cycles AC-3
Control circuit type	AC at 50 Hz
Control circuit voltage limits	0.85...1.1 U _c (-5...55 °C):operational 50 Hz 0.3...0.6 U _c (-5...55 °C):drop-out 50 Hz
Inrush power in VA	160 VA 50 Hz cos phi 0.75 (at 20 °C) 140 VA 60 Hz cos phi 0.75 (at 20 °C)
Hold-in power consumption in VA	15 VA 50 Hz cos phi 0.3 (at 20 °C) 13 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	6...10 W for control circuit
Operating time	20...26 ms on closing 8...12 ms on opening
Maximum operating rate	1200 cyc/h 60 °C
Connections - terminals	Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...4 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 2.5...25 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 2.5...10 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 2.5...25 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 2.5...16 mm ² - cable stiffness: solid without cable end
Tightening torque	Control circuit: 1.2 N.m Power circuit: 5 N.m
Auxiliary contact composition	1 NO + 1 NC
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
mounting support	Plate DIN rail

Environment

Standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1
Product certifications	EAC CE
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH (pollution degree 3) conforming to IEC 60068-2-30 test Db

Permissible ambient air temperature around the device	-20...70 °C at Uc -60...80 °C storage -5...55 °C operation
Operating altitude	3000 m without derating
Fire resistance	850 °C conforming to IEC 60695-2-1
Mechanical robustness	Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (6 Gn for 11 ms) Shocks contactor closed (7 Gn for 11 ms)
Height	127 mm
Width	75 mm
Depth	114 mm
net weight	0.98 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	12.500 cm
Package 1 Length	13.000 cm
Package 1 Weight	983.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	9
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.135 kg
Unit Type of Package 3	P06
Number of Units in Package 3	144
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	154.160 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhân sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch **RoHS/REACH**

Hiệu suất sức khỏe

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Chứng nhận & Tiêu chuẩn

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)