Specifications



Signalling auxiliary contacts, TeSys Ultra, 1 NO and 1 NC

LUA1C11

Product availability: Stock - Normally stocked in distribution facility

Price*: 34.50 USD

Main

| Range | TeSys |
|---------------------------|-------------------|
| Device short name | LUA1 |
| Product or Component Type | Auxiliary contact |

Complementary

| Auxiliary contact composition | 1 NO + 1 NC |
|---------------------------------------------|--------------------------------------------------------------|
| Signalling function | Fault signalling Indicating rotary knob in ready position |
| [Ue] rated operational voltage | <= 250 V AC <= 250 V DC |
| [Ui] rated insulation voltage | 250 V CSA 250 V IEC 60947-5-1 250 V UL |
| [Ith] conventional free air thermal current | 2.5 A |
| Minimum switching voltage | 17 V |
| Minimum switching current | 5 mA |
| Net Weight | 0.07 lb(US) (0.03 kg) |
| Connections - terminals | screw clamp terminals |

Ordering and shipping details

| Category | US10I1122399 |
|-------------------|---------------|
| Discount Schedule | 0111 |
| GTIN | 3389110367317 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| J | |
|------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 0.8 in (2.0 cm) |
| Package 1 Width | 2.4 in (6.0 cm) |
| Package 1 Length | 3.9 in (10.0 cm) |
| Package 1 Weight | 0.8 oz (24 g) |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Unit Type of Package 2 | S01 |
|------------------------------|-------------------------|
| Number of Units in Package 2 | 30 |
| Package 2 Height | 5.9 in (15 cm) |
| Package 2 Width | 5.9 in (15 cm) |
| Package 2 Length | 15.7 in (40 cm) |
| Package 2 Weight | 35.2 oz (998 g) |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 960 |
| Package 3 Height | 29.5 in (75.0 cm) |
| Package 3 Width | 23.6 in (60.0 cm) |
| Package 3 Length | 31.5 in (80.0 cm) |
| Package 3 Weight | 82.54 lb(US) (37.44 kg) |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Reach Free Of Svhc | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| V Toxic Heavy Metal Free | |
| Mercury Free | |
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |