

# Bảng thông số sản phẩm

Thông số kỹ thuật



## mini Pragma surface enclosure - 1 x 6 modules - plain door

MIP12106

### Main

Range	Resi9
Product name	Resi9 MP
product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	6
Nb of horizontal rows	1
Type of door	Plain
Width	Outside: 160 mm
Height	Outside: 198 mm
Depth	Outside : 95 mm

### Complementary

enclosure mounting	Surface
9 mm pitches	12
Total number of 18 mm modules	6
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth (screwed) with 4 outgoing 1 neutral (screwed) with 4 outgoing
Distribution block outgoing	1 x 16 mm <sup>2</sup> for earth 1 x 16 mm <sup>2</sup> for neutral 1 x 6 mm <sup>2</sup> for earth 1 x 6 mm <sup>2</sup> for neutral 2 x 10 mm <sup>2</sup> for earth 2 x 10 mm <sup>2</sup> for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	74 mm
Colour	Door: white (RAL 9003) Front face: white (RAL 9003)
Market segment	Small commercial Residential

## Environment

Standards	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C Back part: 650 °C Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.550 cm
Package 1 Width	16.000 cm
Package 1 Length	19.800 cm
Package 1 Weight	460.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	18
Package 2 Height	52.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.380 kg
Unit Type of Package 3	P12
Number of Units in Package 3	288
Package 3 Height	120.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	146.080 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO<sub>2</sub> thấp.

**Hướng dẫn đánh giá tính bền vững của sản phẩm** là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch RoHS/REACH

## Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information [Yes](#)

Halogen Free Product

## Chứng nhận & Tiêu chuẩn

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations