

# Bảng thông số sản phẩm

Thông số kỹ thuật



Enclosure, Resi9 MP, flush mounting, 1 row of 4 modules, IP40, translucid door, 1 earth + 1 neutral terminal blocks

MIP22104T

## Main

Range	Resi9
Product name	Resi9 MP
product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	4
Nb of horizontal rows	1
Type of door	Translucid
Width	Wall: 126 mm Outside: 150 mm
Height	Wall: 228 mm Outside: 252 mm
Depth	Outside : 18 mm Wall : 80 mm Total : 98 mm

## Complementary

enclosure mounting	Flush
9 mm pitches	8
Total number of 18 mm modules	4
[In] rated current	50 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
Cable entry	Pre-cutted holes
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth (screwed) with 4 outgoers 1 neutral (screwed) with 4 outgoers
Distribution block outgoers	1 x 16 mm <sup>2</sup> for earth 1 x 16 mm <sup>2</sup> for neutral 1 x 6 mm <sup>2</sup> for earth 1 x 6 mm <sup>2</sup> for neutral 2 x 10 mm <sup>2</sup> for earth 2 x 10 mm <sup>2</sup> for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	76 mm
Colour	Front face: white (RAL 9003) Door: translucid

Market segment	Residential Small commercial
----------------	---------------------------------

## Environment

Standards	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C Back part: 650 °C Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.700 cm
Package 1 Width	15.000 cm
Package 1 Length	25.200 cm
Package 1 Weight	498.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	15
Package 2 Height	52.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.364 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	117.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	145.820 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO<sub>2</sub> thấp.

**Hướng dẫn đánh giá tính bền vững của sản phẩm** là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch **RoHS/REACH**

## Hiệu suất sức khỏe



Mercury Free



Rohs Exemption Information

[Yes](#)



Halogen Free Product

## Chứng nhận & Tiêu chuẩn

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

**China Rohs Regulation**

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations