

# Switch Socket - 15A 250V - 3 phase 3 pole - flat pin - IP66 (grey)

S56C315RPGY

#### Main

Range	WPS
product or component type	Switch and socket-outlet
Colour tint	Light grey

# Complementary

Material	PVC (polyvinyl chloride) UV stabilised
Surface finish	Gloss
Width	101 mm
Height	203 mm
Rated current	15 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	2 gangs
Pin number	3
Device composition	Flat pin
Number of poles	3
mounting mode	Surface mounted

## **Environment**

IP degree of protection IP66

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.8 cm
Package 1 Width	10.1 cm
Package 1 Length	20.2 cm
Package 1 Weight	750 g
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Height	22.1 cm

Package 2 Width	36 cm
Package 2 Length	44.5 cm
Package 2 Weight	9000 g
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	198000 g

#### **Sustainability**

Weee

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration
Rohs Exemption Information	Yes
Mercury Free	

collection and never end up in rubbish bins

The product must be disposed on European Union markets following specific waste