Specifications



# WPS - 20A 500V - 3 phase 4 round pin - combination switched socket (grey)

S56C420GY

### Main

Range of product	WPS	
product or component type	Switched socket	
Rated current	20 A at 500 V AC	
poles description	3P + N	

## Complementary

device mounting	Surface
Switch application	On/off switching
Outlet standard description	Round pin
Number of gangs	1 gang
Material	PVC (polyvinyl chloride) UV stabilised
Cover frame colour tint	Grey
Height	204 mm
Width	101 mm
Depth	104 mm

### Environment

IP degree of protection	IP66
Motor M-rating AS3133	M150
Standards	GB/T 11918:2001

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.5 cm
Package 1 Width	10.4 cm
Package 1 Length	20.8 cm
Package 1 Weight	833.333 g
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Height	22.1 cm
Package 2 Width	36 cm

Package 2 Length	44.5 cm
Package 2 Weight	10000 g
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	218000 g

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins